



PC80X, 110X & 150 - Premium Choice

(Ceiling Mounted Ventilation Fans)



Performance

Model	Duct Size for Test	CFM	Static Pressure (in W.G.)	Energy Efficiency (CFM/Watts)*	Watts	Power (V/Hz)	Sones	Amps
PC80X	4"	80/58	0.1/0.25	3.0	32	120/60	0.4	.27
	6"	80/63					<0.3	
PC110X	4"	96/70	0.1/0.25	3.2	36	120/60	1.1	.30
	6"	110/87					0.6	
PC150	6"	150/110	0.1/0.25	3.8	41	120/60	1.1	.34

* Energy Star qualified data based on tested air flow and power consumption.

Dimensions

Model	Duct Dia.	Grille Size (Sq. in inches)	Cabinet Size (in Inches)			Unit Wgt. (lbs)
			W	D	H	
PC80X	4 or 6"	13 x 14	11-3/8	10-1/2	7-5/8	8
PC110X	4 or 6"	13 x 14	11-3/8	10-1/2	7-5/8	9
PC150	6"	13 x 14	11-3/8	10-1/2	7-5/8	9



Typical Specifications:

Ventilating fan shall be S&P PC80X, PC110X or PC150 mounted in the ceiling. The fan shall have a 5 year limited warranty. The fan shall be HVI Certified at 0.1 inch water gauge for CFM performance above. The motor shall be ETL and cETL Listed with impedance protection plus additional thermal protection. The fan shall be Energy Star Qualified.

For more information contact us at www.solerpalau-usa.com or 1.800.961.7370 for additional submittal drawings.

Soler & Palau will not be responsible for fabrication changes or errors resulting from customer use of a non-current submittal drawing.