

QSLG1000

U.S. Patent No. 8,701,261



The safe & affordable install

Applicable for residential or light commercial installations



Quick-Sling SPECS QSLG1000

A Close Up:



Each arm attaches to wood using 2 zip screws for install purposes & a 4" through bolt & nut for security. Installs to steel using steel beam adapters.



12 points of anti-vibration isolation is provided using four 50-derometer self-adhesive rubber pads & 16 rubber washers.

Extension arms individually adjust in one inch increments using screws & nuts for speed & versatility. Installs as high as 36" or as low as 48" on flat or pitched roofs.



32" secondary drain pan hangers are provided & install in seconds.

*Drain pan not included.



Our Quick-Sling is made of 14-gauge square, steel tubing which not only cuts down on vibration but is also able to hold up to 300 lbs.

3 Dimensionally Adjustable

Height: 36" to 48"

Width: 32" to 48"

Length: 32" to 48"

*Powder Coated.

Quick-Sling provides you with a non-swinging, solid platform that is quick, safe, stable and affordable.

Quick-Sling 391 West Water Street Taunton, MA 02780

P:1.800.699.0453 F:1.800.699.0423

www.Quick-Sling.com

*As of 1/1/2015 Quick-Sling offers a 2-year warranty on steel & workmanship; Quick-Sling products are coated in accordance with ASTM D3451-06.