


## The safe & affordable install

*Applicable for residential or light commercial installations*



### Mini Split 1200/1201 SPECS

#### A Close Up:



Each foot is slotted to receive 1/4"/20 hardware, which allows the stand to bolt to concrete, cement, or wood for security and stability.



Our Mini Split Stand is made of 14-gauge square, steel tubing.

Holds up to 400 lbs.

\*Powder Coated.



4 points of anti-vibration isolation washers are provided while using four 50-derometer rubber pads on each foot.



Available in 2 depths:  
QSMS1200-Thin QSMS1201-Wide  
Adjustable in length from 34" to 40" in 1" increments.  
Our 12" high Mini Split Stand fits all units on the market.  
See compatibility charts at [www.quick-sling.com](http://www.quick-sling.com). All necessary hardware is provided.



Quick-Sling's Mini Split stand provides an elevated platform that is quick, safe, stable, and affordable.

Quick-Sling 391 West Water Street Taunton, MA 02780

P:1.800.699.0453 F:1.800.699.0423  
[www.Quick-Sling.com](http://www.Quick-Sling.com)

\*As of 1/1/2015 Quick-Sling offers a 2-year warranty on steel & workmanship; Quick-Sling products are coated in accordance with ASTM D3451-06.